

ENTOFOG TS35S


Thermal Fogging Machine

GERMAN TECHNOLOGY


Tested by



Reliable Carburetor System



Robust Formulation Tank



Durable Protective Cover



Oil Based & Water Based Fog Tube

AFTER-SALES SUPPORT SERVICE



Technical Specification

Weight (empty)	8 kg
Dimension (L x W x H)	137.5 x 27 x 34 cm
Solution tank capacity	5.5 l
Fuel consumption	2 l/h
Performance of engine	18.7 kw / 25.4 hp
Maximum flow rate	42 l/h
Effective horizontal reach	* >100 m (oil based) * >40 m (water based with FX Hidro)
Power supply	4 x 1.5 volt
Starting device	Manual (most durable system)
Droplet size spectrum	* <25 microns (oil based) * <150 microns (water based)



Characteristics

The Entofog TS35S thermal fogging machine has been the best choice for Vector , Pest Control , Disinfection , Public Health , Plant Protection , Stored Product Control.

This unit has been designed for use with insecticides, acaricides, fungicides , and disinfectant! Light weight for convenient use in areas where poor roads and track make it difficult to handle heavy equipment. The only mass produced unit with a covered air intake valve, Providing a silencer effect and protection against dust and solution particles.



Syarikat Perniagaan Kemuncak (000640840-P)

No. 43, Jalan Meranti Jaya 12, Meranti Jaya Industrial Park,
47120 Puchong, Selangor Darul Ehsan, Malaysia.

Tel : 03-8061 8346

Office h/p : 012-369 4346

Fax : 03-8060 1180

Website : www.syarikatkemuncak.com.my Email : kemuncak56@gmail.com